

ELETTROPOMPA SOMMERSA INOX PER DRENAGGIO STAINLESS STEEL SUBMERSIBLE DRAINAGE PUMP

LIMITI D'IMPIEGO

- Temperatura liquido fino a 35°C
(per un uso domestico secondo EN 60335-2-41)
Temperatura max. liquido: 35°C (per altri impieghi)
- Profondità d'immersione 5 mt.
- Passaggio solidi Ø 2 mm
- Livello min. d'aspirazione 2 mm

MOTORE

- Protezione amperometrica a riarmo automatico incorporata
- Condensatore permanente inserito
- Isolamento Classe F
- Protezione IP 68
- Cavo alimentazione 10 mt.

MATERIALI

- Maniglia Polipropilene
- Corpo pompa Acciaio Inox
- Girante Noryl
- Cassa motore Acciaio Inox
- Albero motore Acciaio Inox
- Doppio anello di tenuta

OPERATING CONDITIONS

- Liquid temperature up to 35°C
(for home use according to EN 60335-2-41)
Temperature max. liquid: 35°C (for other uses)
- Submersion depth 5 mt.
- Grain size inlet Ø 2 mm
- Min. suction level 2 mm

MOTOR

- Built-in overload motor protector with automatic reset
- Permanent split capacitor
- Insulation Class F
- Protection IP 68
- Power cable 10 mt.

MATERIALS

- Handle Moplen
- Pump body Stainless Steel
- Impeller Noryl
- Motor casing Stainless Steel
- Shaft with rotor Stainless Steel
- Double oil seal



SDX 350/S

TIPO - TYPE	
P1	350 W
Voltage	230 V
Frequency	50 Hz
Ampere	1,7 A
Q max.	150 l/1'
H max.	7 m
DNM - DNA	1" 1/4
Dimensions (P x L x H)	206 x 231 x 310 mm
Weight	5,3 kg

